

# Technical Data Sheet

## LOXEAL ACTIVATOR 11

### FOR ANAEROBIC ADHESIVES AND SEALANTS

#### Description

It cleans, degreases parts and speeds up anaerobic adhesives and sealants fixture time.

Curing effect is obtained in 20 - 120 seconds depending on type of adhesive, gap between parts and room temperature; wait for solvent evaporation before assembling parts.

It can be used either on flange or threaded joints; its use might reduce final mechanical strength.

The Activator is applied on one surface and let to dry for a few seconds.

#### Physical properties

Composition : organic chemicals in solvent  
Appearance : green  
Viscosity (+25°C - mPa s) : 1 - 2 mPa.s  
Specific weight at +25°C (g/ml) : 0,8  
Flash point (COC/DIN/ISO 2592) : +21°C  
Activation effect on surface : 24 hours  
Shelf life : 1 year at +25°C in original unopened packaging

Breakaway locking torque (ISO 10964) after 5' : >5 Nm  
(Ref. AE 83-54)

#### Storage

We recommend to store product in a cool and dry place at temperature non exceeding +25°C.

To avoid contaminations do not refill containers with used product. For more information on applications, storage and handling contact Loxeal Technical Service

#### Safety and handling

Consult the Safety Data Sheet before use.

#### Note

The data contained herein, obtained in Loxeal laboratories, are given for information only; if specifics are required, please contact Loxeal Technical Department. Loxeal ensures abiding quality of supplied products according to its own specifics. Loxeal cannot assume responsibility for the results obtained by others which methods are not under Loxeal control. It is user's responsibility to determine suitability for user's purpose of any product mentioned herein. Loxeal disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Loxeal products. Loxeal specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.